

MATERIAL SAFETY DATA SHEET

Trade Name: AG3 – New Formulation

Date: July 2005

Issue: 2

1. IDENTIFICATION OF THE CHEMICAL AND OF THE MANUFACTURER, IMPORTER OR OTHER UNDERTAKING		
1.1	Identification of the substance or preparation	Farécla G3 Advanced Liquid Rubbing Compound
	Trade name	Advanced G3
	Code of the preparation	AG3CSF
1.2	Identification of the manufacturer, importer or other undertaking	
1.2.1	Manufacturer	Farécla Products Limited
1.2.2	Street address	Farécla Products Ltd Broadmeads Ware SG12 9HS England
	Telephone Number	+44 (0)1920 465 041
	Telefax	+44 (0)1920 466 557
	E-Mail	enquiries@farecla.com
	Website	www.farecla.com
1.2.3	Name & address of the informant in emergency cases	Farécla Products Ltd Ware, England
	Emergency telephone number	+44 (0)1920 465041 09.00 – 17.00 GMT Mon-Thurs 09.00 – 15.45 – Fri

2. COMPOSITION AND INFORMATION ON INGREDIENTS						
2.1	Ingredients	CAS No	EC No.	Weight %	Symbols	R Phrases
	Kerosine	8008-20-6	232-366-4	5 – 10	Xn, N	10,38,51/53,65
	White Spirit	64742-88-7	265-191-7	5 – 10	Xn,N	10,51/53,65,66
	Pine Oil	8002-09-3	-	< 3	Xi,	36/37/38

3. HAZARDS IDENTIFICATION	
3.1	<p>Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R52/53)</p> <p>See Section 8, 11, 12 & 13 for first bullet (as CHIP now covers environmental hazards)</p> <p>See Section 16.1 for ingredient R-Phrases.</p>

4. FIRST AID MEASURES		
4.1	Inhalation	Remove patient to fresh air. Keep warm and at rest. Seek medical attention if ill effects occur.
4.3	Contact with Skin	Wash affected area with plenty of soap and water. Seek medical attention if irritation persists.
4.4	Contact with eyes	If substance has got into eyes, immediately with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
4.5.	Ingestion	Give water or milk to drink. Do not induce vomiting. Seek medical attention if ill effects occur.
4.6.	Other information.	See Section 11.

5. FIRE-FIGHTING MEASURES		
5.1	Suitable extinguishing media	In case of fire use Foam, dry agent (S43) powder, carbon dioxide.
5.2	Exposure hazards during fire	May give off noxious fumes in a fire.

6. ACCIDENTAL RELEASE MEASURES		
6.1	Personal precautions	Spillage causes slippery surface. Shut off all ignition sources.
6.2	Methods for cleaning up	Absorb spillage in inert material and shovel up. Ventilate the area and wash spill site after material pick-up is complete.

7. HANDLING AND STORAGE		
7.1	Handling	The usual precautions for handling chemical products should be observed. Ensure adequate ventilation. Do not breathe the dry product dust.
7.2	Storage	Keep in a cool, dry place.

8 EXPOSURE CONTROL / PERSONAL PROTECTION	
8.1	General - Use good personal hygiene practices. Wear Nitrile gloves. Change gloves at least daily.
	Kerosine No exposure limits have been set for this
	White Spirit OES/LTEL 100 ppm 600 mg/m ³ OES/STEL --- ppm --- mg/m ³ (USA) TLV (TWA) 100 ppm 525 mg/m ³
	Pine Oil No exposure limits have been set for this

9. PHYSICAL AND CHEMICAL PROPERTIES		
9.1	Physical state, colour and odour	White liquid paste with mild paraffinic odour, partly miscible with water.
9.2	pH#	8.6
9.3	Information on changes in the physical state	
9.3.1	Boiling point / boiling range	Not applicable
9.3.2	Flashpoint	63 deg C (CC)
9.3.3	Melting Point	Not applicable
9.4	Auto ignition point	> 250 deg C
9.5	Partition Coefficient: D-Octanol/Water	Not known
9.6	Vapour pressure	Not available
9.7	Relative density	1.47
9.8	Solubility a) water solubility b) fat solubility	Partial Not known
9.9	Viscosity	Ca 20,000 cps (Ferranti) at 20 deg C

10. STABILITY AND REACTIVITY		
10.1	Materials to avoid	None
10.2	Hazardous decomposition products	None known

11. TOXICOLOGICAL INFORMATION		
11.1	Information	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness May cause gastrointestinal disturbances


12 ECOLOGICAL INFORMATION		
12.1	Information	Hazardous to the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R52/53)

13. DISPOSAL CONSIDERATIONS								
13.1	Disposal	<p>This material and its container must be disposed of as hazardous waste (S60).</p> <p>Disposal should be in accordance with local, state or national legislation.</p> <p>Incineration by an approved method could be considered.</p>						
13.2	Solid Content	<table> <tr> <td>1 litre bottle</td> <td>959.50g</td> </tr> <tr> <td>500ml bottle</td> <td>479.75g</td> </tr> <tr> <td>1 US Gallon</td> <td>3556.30g</td> </tr> </table>	1 litre bottle	959.50g	500ml bottle	479.75g	1 US Gallon	3556.30g
1 litre bottle	959.50g							
500ml bottle	479.75g							
1 US Gallon	3556.30g							

14. TRANSPORT INFORMATION		
14.1	UN number	Not applicable
14.2	Packaging category	Not applicable
14.3	Land transport	Not applicable
14.4	Sea Transport	Not applicable
14.5	Air transport	Not applicable
14.5.2	Correct technical name	Abrasive rubbing compound.
14.5.3	Other information	Not classified as hazardous for transport.

15. REGULATORY INFORMATION		
15.1	Information on the warning label	Not classified as hazardous to users.
<p>This product is covered by Dangerous Preparations Directive (1999/45/EC) as amended.</p> <p>Refer to current Chemicals (Hazardous Information and Packaging) Regulations.</p> <p>This Safety Data Sheet is provided in compliance with the Safety Data Sheets Directive (91/155/EC).</p> <p>The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents.</p> <p>The product on the MSDS contains all chemicals reported under TSCA.</p> <p>The product contains no chemicals, forms or categories reportable under EPCRA Section 313.</p>		
15.2	Risk Phrases	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R52/53)
15.3	Safety Phrases	This material and its container must be disposed of as hazardous waste (S60)

16. OTHER INFORMATION		
16.1	<p>R10: Flammable</p> <p>R36/37/38: Irritating to eyes, respiratory system and skin.</p> <p>R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65: Harmful: may cause lung damage if swallowed.</p> <p>R66: Repeated exposure may cause skin dryness or cracking.</p>	
16.2	Purpose of use expressed in writing	Finishing of painted and lacquered finishes.

16. OTHER INFORMATION cont.		
16.3	Directions for use	Data sheets providing directions for use are available from Farécla Products Limited.
16.4	Other information	<p>To the best of our knowledge, the information contained herein is accurate.</p> <p>However, Farécla Products Limited assumes no liability whatsoever for the accuracy of the information.</p> <p>Final determination of the suitability of any material is the sole responsibility of the user.</p> <p>All materials may present unknown hazards and should be used with caution and in accordance with the recommended methods of application.</p>
16.4	Additional information	<p>Water Hazard Class: 1 = slight, 2 = medium, 3 = severe hazard.</p> <p>NA = not applicable, NC = not classified, ND = no data, TWA = time-weighted average.</p> <p>LTEL= 8hr TWA; SEL= 15min TWA; ppm = parts per million.</p> <p>### = changes to section since last revision</p>
16.5	Sources of information used in the compilation of the safety data sheet	The information in the MSDS has been compiled according to U.S. regulations (HCS & ANSI Standards)
Reasons for the confidentiality of the information:		The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary. We reserve the right to withhold information on the ingredients in the interest of protecting our formula.
Date:		July 2005
Signature: 		Robert Wilkinson R + D Director